



Modelo Model	LPL06236	LPL12236	LPL12258
Sensor Sensor	No	No	No
Tensión entrada nominal Input voltage	230V	230V	230V
Frecuencia entrada nominal Input frequency	50Hz	50Hz	50Hz
Rango de frecuencia de entrada Input frequency range	50-60Hz	50-60Hz	50-60Hz
Potencia Power	22W	22W	43W
Número de LEDs Number of LEDs	280 LEDs SMD	308 LEDs SMD	602 LEDs SMD
Flujo luminoso Lumen	1951Lm	1997Lm	3927Lm
Temperatura de color Color temperature	6000K <input type="checkbox"/>	6000K <input type="checkbox"/>	6000K <input type="checkbox"/>
Ángulo Angle	120°	120°	120°
Largo Length	600mm	1200mm	1200mm
Ancho x Alto Width x Height	85 x 65mm	85 x 65mm	85 x 65mm
Base y Difusor Base and Diffuser	Policarbonato transparente Transparent PC		
Grapa de montaje y Clips de cierre Mounting clamp and Closing clips	Acero inoxidable Stainless Steel		
IP	65		



Pantallas
Estancas

Pantalla
Estanca LED

22W
43W



Somos transparentes

No escondemos nada, todo queda a la vista. Las nuevas pantallas LED fabricadas íntegramente con policarbonato transparente, ofrecen características inigualables, alta luminosidad, menor tamaño, ligereza, ultra bajo consumo y excelente resistencia. Cierres inoxidables incluidos en todos los modelos.

We are all about transparency

We hide nothing, it is all out to be seen. Our new LED fitting are fully manufactured in transparent polycarbonate, offering remarkable features like high luminosity, smaller size, light weight, ultra low consumption and excellent durability. Stainless closures are included.



LPL06236



LPL12236



LPL12258



Videos demostrativos:
www.priled.eu/videos.html

