



Modelo Model	LPL061224VN	LPL091224VN	LPL121224VN
Rango de tensión Voltage range	12V-24V DC	12V-24V DC	12V-24V DC
Potencia Power	20W	20W	40W
Número de LEDs Number of LEDs	280 LEDs SMD	308 LEDs SMD	602 LEDs SMD
Flujo luminoso Lumen	1951Lm	1997Lm	3927Lm
Temperatura d color Color temperature	6000K	6000K	6000K
Ángulo Angle	120°	120°	120°
Largo Length	630mm	1230mm	1230mm
Ancho x alto Width x height	120x71mm	120x71mm	120x71mm
Base y difusor Base and diffuser		PC	
IP		65	
FP		>0,90	



Sistema rápido de instalación.

No es necesario abrir la pantalla para cablear, realice la operación mediante los registros dedicados.



Pantalla
Estanca LED
Neophos
12V-24V DC



Baja tensión.

El consumo cobra más importancia, si cabe, cuando la energía proviene de baterías ya que el rendimiento es un factor clave. Duplicar la autonomía es sencillo con solo cambiar de iluminación convencional a LED.

Este modelo está también especialmente recomendado para usos con obligación de baja tensión como entornos de piscinas, fosos...

Low Voltage.

Consumption becomes even more important when the power comes from batteries, efficiency is a key factor. Duplicate autonomy is simple just changing conventional lighting to LED.

This model is also especially recommended for use with low voltage duty environments like pools, ditches...

12V-24V DC



LPL061224VN



LPL091224VN
LPL121224VN



Videos demostrativos:
www.priLED.eu/videos.html

