



Modelo Model	PU0683SF PU0684SF PU0686SF	PU1283SF PU1284SF PU1286SF	PU1583SF PU1584SF PU1586SF
Equivalencia Equivalence	Tubo de 18W 18W tube	Tubo de 36W 36W tube	Tubo de 58W 58W tube
Longitud Lenght	60cm	120cm	150cm
Diámetro Diameter	28mm	28mm	28mm
Potencia Power	10,7W	20,1W	23,8W
Número de LEDs Number of LEDs	96	192	240
Radiador Radiator	Aluminio de alta disipación Aluminum of high dissipation	Aluminio de alta disipación Aluminum of high dissipation	Aluminio de alta disipación Aluminum of high dissipation
Cubierta Covering	Polycarbonato Opal Opal polycarbonate	Polycarbonato Opal Opal polycarbonate	Polycarbonato Opal Opal polycarbonate
Temperatura de color Color temperature	3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 6000K <input type="checkbox"/>	3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 6000K <input type="checkbox"/>	3000K <input type="checkbox"/> 4000K <input type="checkbox"/> 6000K <input type="checkbox"/>
Lúmenes Lumen	1093Lm	2053Lm	2431Lm
Vida media Chip Chip average lifetime	50.000h	50.000h	50.000h
CRI	80	80	80
Ángulo Angle	120°	120°	120°



Tub-LED 0.6-1.2-1.5



Encuentra la posición perfecta

El casquillo giratorio equipado en todos nuestros tubos LED permite, independientemente del tipo y posición del portatubo en el equipo original, orientar el haz de luz hacia el lugar deseado. Tan sólo sitúe los extremos en el ángulo deseado e instale el tubo, así de fácil.

Find the right positioning

The spinning housing featured in all our LED tubes allows for a custom light focus orientation, independently of the type and placement of the original tube holder. Simply position the edges in the right angle and proceed to install the tube.



PU0683SF - PU0684SF - PU0686SF
PU1283SF - PU1284SF - PU1286SF
PU1583SF - PU1584SF - PU1586SF

Tub-LED



Videos demostrativos:
www.priLED.eu/videos.html

